

TOUGHROAD SLR 1



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Copper
FRAME	ALUXX SLR grade aluminium
FORK	Composite with alloy OverDrive steerer, low-rider rack mounts
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact, low-rise, 31.8mm
STEM	Giant Contact, 8 degree
SEATPOST	Giant D-Fuse, Composite
SADDLE	Giant Contact Comfort, Neutral
PEDALS	Platform
DRIVETRAIN	
SHIFTERS	Shimano Deore, 20sp
FRONT DERAILLEUR	Shimano Deore
REAR DERAILLEUR	Shimano Deore Shadow+
BRAKES	Shimano MT400 hydraulic disc, 160mm
BRAKE LEVERS	Shimano MT401 hydraulic
CASSETTE	Shimano HG500, 11-42T, 10sp
CHAIN	KMC X10-1
CRANKSET	FSA V-Drive, 32-44T
WHEELS	
BOTTOM BRACKET	FSA sealed
RIMS	Giant SX2 disc tubeless
HUBS	Giant sport disc, 28H
SPOKES	Stainless steel, 14g
TIRES	Giant Sycamore, FlatGuard Deflect 2, 700x50c
EXTRAS	Front and rear racks, X-Defender down tube protector

FEATURES

- Frame: ALUXX SLR grade aluminium
- Fork: Composite with alloy OverDrive steerer, low-rider rack mounts
- Shifters: Shimano Deore, 20sp
- Crankset: FSA V-Drive, 32-44T
- Colours: Copper

Price: \$1,799

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	420	460	510	550
Seat Tube Angle	73.0°	73.0°	72.0°	71.5°
Top Tube Length (mm)	585	595	605	620
Head Tube Length (mm)	125	150	170	190
Head Tube Angle	71.5°	71.5°	72.0°	72.0°
Fork Rake (mm)	42	42	42	42
Trail (mm)	78.3	78.3	74.9	74.9
Wheelbase (mm)	1067	1078	1071	1080
Chain Stay Length (mm)	450	450	450	450
Bottom Bracket Drop (mm)	70	70	70	70
Stack (mm)	578	602	623	642
Reach (mm)	408	411	403	405
Stand Over Height (mm)	724	754	795	864
Stem Length (mm)	90	100	110	110
Crank Length (mm)	170	175	175	175
Wheel Size	700C	700C	700C	700C

*All specifications listed are subject to change without notice. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.*