

# REIGN E+ 0 PRO 25KM/H



## SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Chameleon Green / Gold
FRAME	ALUXX SL grade aluminium, Maestro, 160mm travel, Boost
FORK	Fox 36 Float Factory, Kashima Coat, GRIP 2 Damper, 15x110mm Kabolt Axle, OverDrive steerer, 170mm travel
SHOCK	Fox Float X2 Factory, Kashima Coat, 2 position lever, Trunnion mount
COMPONENTS	
HANDLEBAR	Giant Contact SL trail rise, 35mm
STEM	Giant Contact SL, 35mm, 8 degree
SEATPOST	RockShox Reverb AXS dropper, 30.9mm
SADDLE	Giant Contact SL, Neutral
PEDALS	-
DRIVETRAIN	
SHIFTERS	SRAM AXS Eagle, 12sp
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM X01 AXS Eagle
BRAKES	SRAM Code R hydraulic disc, Fr: 220mm, Rr: 200mm
BRAKE LEVERS	SRAM Code R hydraulic
CASSETTE	SRAM PG1230 Eagle, 11-50T, 12sp
CHAIN	SRAM X01 Eagle
CRANKSET	Praxis Carbon, 36T
WHEELS	
BOTTOM BRACKET	N/A
RIMS	Giant eTRX Hookless Composite, DBL, WheelSystem
HUBS	Giant eTRX Hookless Composite, DBL, WheelSystem, 28H
SPOKES	Giant eTRX Hookless Composite, DBL, WheelSystem
TIRES	Fr: Maxxis Minion DHF, TR, EXO, 3C, Folding, 27.5x2.6" Rr: Maxxis Minion DHR II, TR, EXO, 3C, Folding, 27.5x2.6"
EXTRAS	Giant EnergyPak Smart 6A charger, MRP chain guide
HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro, powered by YAMAHA
SENSORS	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl ONE, Remote button
BATTERY	Giant EnergyPak 500, 36V integrated Lithium-Ion

## FEATURES

- Frame: ALUXX SL grade aluminium, Maestro, 160mm travel, Boost
- Fork: Fox 36 Float Factory, Kashima Coat, GRIP 2 Damper, 15x110mm Kabolt Axle, OverDrive steerer, 170mm travel
- Shifters: SRAM AXS Eagle, 12sp
- Crankset: Praxis Carbon, 36T
- Colours: Chameleon Green / Gold

Price: \$11,499

## GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	406	445	482	507
Seat Tube Angle	76.0°	76.0°	76.0°	76.0°
Top Tube Length (mm)	595	620	645	670
Head Tube Length (mm)	100	110	120	130
Head Tube Angle	64.5°	64.5°	64.5°	64.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	124.3	124.3	124.3	124.3
Wheelbase (mm)	1223	1249	1276	1303
Chain Stay Length (mm)	470	470	470	470
Bottom Bracket Drop (mm)	15	15	15	15
Stack (mm)	592	602	611	620
Reach (mm)	430	452	475	497
Stem Length (mm)	40	40	50	50
Crank Length (mm)	160	160	165	165
Wheel Size	27.5	27.5	27.5	27.5

All specifications listed are subject to change without notice. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.