

FASTROAD SL 2



SPECS

FRAME	
SIZES	S, M, M/L, L, XL
COLOURS	Metallic Navy
FRAME	ALUXX SL grade aluminium
FORK	Composite, with alloy OverDrive steerer
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect, 31.8mm
STEM	Giant Sport, 7 Degree
SEATPOST	Giant D-Fuse, Alloy
SADDLE	Giant Contact, Neutral
PEDALS	Resin Anti-slip
DRIVETRAIN	
SHIFTERS	Shimano Sora, 18sp
FRONT DERAILLEUR	Shimano Sora
REAR DERAILLEUR	Shimano Sora
BRAKES	Tektro HD-R210 hydraulic disc, 140mm
BRAKE LEVERS	Tektro HD-R210 hydraulic
CASSETTE	Shimano HG201, 11-34T, 9sp
CHAIN	KMC X9
CRANKSET	FSA Omega, 34-50T
WHEELS	
BOTTOM BRACKET	FSA sealed
RIMS	Giant alloy disc
HUBS	Giant alloy cassette disc, 28H
SPOKES	Stainless steel, 14g
TIRES	Giant S-R3, 700x32c

FEATURES

- Frame: ALUXX SL grade aluminium
- Fork: Composite, with alloy OverDrive steerer
- Shifters: Shimano Sora, 18sp
- Crankset: FSA Omega, 34-50T
- Colours: Metallic Navy

Price: \$1,099

GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (mm)	445	460	490	520	550
Seat Tube Angle	73.5°	73.0°	73.0°	72.5°	72.5°
Top Tube Length (mm)	545	560	575	595	615
Head Tube Length (mm)	130	155	180	200	225
Head Tube Angle	71.5°	72.0°	72.0°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	64.7	61.5	61.5	58.2	58.2
Wheelbase (mm)	1014	1020	1035	1045	1065
Chain Stay Length (mm)	425	425	425	425	425
Bottom Bracket Drop (mm)	70	70	70	70	70
Stack (mm)	537	563	586	607	631
Reach (mm)	386	388	395	403	416
Stand Over Height (mm)	697	719	741	767	795
Stem Length (mm)	90	100	100	110	110
Crank Length (mm)	170	172.5	172.5	175	175
Wheel Size	700C	700C	700C	700C	700C

*All specifications listed are subject to change without notice. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.*