

STANCE 29

TECHNOLOGIES:



INTRODUCTION

Float through rock gardens. Feel the flow on technical singletrack. This full-suspension 29er makes it easy to experience the latest trail-taming technologies for a smooth, confident ride.

STANCE 29 2

FRAME	
Sizes	S, M, L, XL
Colour	Gunmetal Black
Frame	ALUXX grade aluminium, FlexPoint, 120mm travel
Fork	SR Suntour Raidon 34, LOR, OverDrive steerer, 15x110mm axle, 130mm or Giant Crest 34 RCL, 130mm
Shock	SR Suntour Raidon R
COMPONENTS	
Handlebar	Giant Connect trail riser, 31.8mm
Stem	Giant Contact, 8 degree
Seat Post	Giant Alloy, 30.9mm
Saddle	Giant Romero
DRIVETRAIN	
Shifters	Shimano Deore, 12sp
Rear Derailleur	Shimano Deore Shadow+
Brakes	Shimano MT200 hydraulic disc, Fr: 180mm, Rr: 160mm
Brake Levers	Shimano MT201 hydraulic
Cassette	Shimano Deore, 10-51T, 12sp
Chain	Shimano Deore
Crankset	Praxis Cadet, 30T
Bottom Bracket	Praxis press fit
WHEELS	
Rims	Giant XCT, tubeless
Hubs	Shimano MT-410, 28H
Spokes	Stainless steel, 14g
Tyres	Maxxis Forekaster TR, EXO, 29x2.35"
OTHER	
Extras	Giant chain guide

OVERVIEW

Modern mountain bike trails are fun, flowy and challenging. Stance 29 gets you in sync with the terrain, so you can ride with more confidence and have more fun. The lightweight and durable ALUXX aluminium frame features our FlexPoint rear suspension system for a smooth, balanced ride that keeps you in control. It gives you 120mm of smooth suspension travel in the rear and 130mm up front. Combine that with the added stability of 29-inch wheels and you get a confident ride to help you crush challenging descents and climb with greater traction and speed.

KEY PERFORMANCE FACTORS

Attainable trail performance: Handcrafted with lightweight, stiff and durable ALUXX aluminium, it's the perfect entry to full-suspension performance.

Smooth suspension: FlexPoint Suspension technology helps you tackle challenging terrain and improve your trail riding capabilities.

29er confidence and control: Larger 29-inch diameter wheels roll over rugged terrain with balance and stability, giving you the momentum to tackle technical climbs and the confidence to fly on fast, rugged singletrack descents.

FRAME GEOMETRY

UNITS IN MM UNLESS OTHERWISE INDICATED.

FRAME	S	M	L	XL
Seattube Length	338	431	482	507
Seattube Angle (Degrees)	75.00	75.00	75.00	75.00
Toptube Length	570	593	624	645
Headtube Length	100	100	125	140
Headtube Angle (Degrees)	67.50	67.50	67.50	67.50
Fork Rake	51	51	51	51
Trail	100	100	100	100
Wheelbase	1134	1157	1192	1215
Chainstay Length	438	438	438	438
Bottom Bracket Drop	40	40	40	40
Stack	612	612	635	668
Reach	406	429	454	471
Standover Height	730	734	763	782
Stem Length	50	50	60	70
Crank Length	165.0	170.0	170.0	170.0
Wheel Size	29"	29"	29"	29"

SKU

PLEASE QUOTE PART NUMBERS WHEN ORDERING TO ENSURE YOU RECEIVE THE CORRECT PRODUCT.

MODEL	S	M	L	XL
Stance 29 2	2111006104	2111006105	2111006107	2111006108
Stance 29 2 (Crest fork)	2111006504	2111006505	2111006507	2111006508